

Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 18-7813-1
 Version Number:
 3.00

 Issue Date:
 01/28/16
 Supercedes Date:
 05/29/14

Product identifier

3M Unitek Transbond LR Capsule Kit (712-033)

ID Number(s):

70-2020-8945-7

Recommended use

Orthodontic use. Orthodontic use

Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

11-9309-3, 11-9681-5

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

3M Unitek Transbond LR Capsule Kit (712-033) 01/28/16

12/29/17



Safety Data Sheet

Copyright,2017,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 11-9309-3 **Version Number:** 9.01 **Issue Date:** 12/29/17 **Supercedes Date:** 02/25/16

SECTION 1: Identification

1.1. Product identifier

3M Unitek Transbond XT Primer (712-034)

Product Identification Numbers

70-2020-8946-5

1.2. Recommended use and restrictions on use

Recommended use

Orthodontic use, Orthodontic use

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Page 1 of 10

Pictograms



Hazard Statements

Causes eye irritation.

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
BISPHENOL A DIGLYCIDYL ETHER	1565-94-2	45 - 55 Trade Secret *
DIMETHACRYLATE		
TRIETHYLENE GLYCOL DIMETHACRYLATE	109-16-0	45 - 55 Trade Secret *
TRIPHENYLANTIMONY	603-36-1	< 1 Trade Secret *
4-(DIMETHYLAMINO)-BENZENEETHANOL	50438-75-0	< 0.5 Trade Secret *
DL-CAMPHORQUINONE	10373-78-1	< 0.3 Trade Secret *
HYDROQUINONE	123-31-9	< 0.03 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Page 2 of 10

12/29/17

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide Carbon dioxide

Condition

During Combustion During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated

Page 3 **of** 10

12/29/17

work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
HYDROQUINONE	123-31-9	ACGIH	TWA:1 mg/m3	A3: Confirmed animal
			_	carcin., Dermal
				Sensitizer
HYDROOUINONE	123-31-9	OSHA	TWA:2 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form: Liquid

Odor, Color, Grade: Clear to yellow in color, slight acrylate odor

Odor thresholdNo Data AvailablepHNot ApplicableMelting pointNot ApplicableBoiling PointNot Applicable

Flash Point > 220 °F [Test Method: Closed Cup] [Details: Polymerizes]

Page 4 of 10

3M Unitek Transbond XT Primer (712-034)

12/29/17

Evaporation rate No Data Available Flammability (solid, gas) Not Applicable Flammable Limits(LEL) Not Applicable Not Applicable Flammable Limits(UEL)

Vapor Pressure <= 16 psia [@ 131 °F] [Ref Std:AIR=1]

Vapor Density No Data Available

Density 1.14 g/ml [Ref Std:WATER=1] **Specific Gravity** 1.14 [*Ref Std*:WATER=1]

Solubility in Water

Solubility- non-water No Data Available Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available

175 centistoke [@ 73.4 °F] Viscosity

Molecular weight No Data Available **Volatile Organic Compounds** No Data Available

Percent volatile

VOC Less H2O & Exempt Solvents No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Light

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of

10

the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
TRIETHYLENE GLYCOL DIMETHACRYLATE	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
TRIETHYLENE GLYCOL DIMETHACRYLATE	Ingestion	Rat	LD50 10,837 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Dermal	Professio nal judgeme nt	LD50 estimated to be 2,000 - 5,000 mg/kg
TRIPHENYLANTIMONY	Inhalation- Dust/Mist		LC50 estimated to be 1 - 5 mg/l
TRIPHENYLANTIMONY	Dermal	Rat	LD50 > 2,000 mg/kg
TRIPHENYLANTIMONY	Ingestion	Rat	LD50 82.5 mg/kg
DL-CAMPHORQUINONE	Dermal	Professio nal judgeme nt	LD50 estimated to be 2,000 - 5,000 mg/kg
DL-CAMPHORQUINONE	Ingestion	Rat	LD50 > 2,000 mg/kg
HYDROQUINONE	Dermal	Rat	LD50 > 4,800 mg/kg
HYDROQUINONE	Ingestion	Rat	LD50 302 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
TRIETHYLENE GLYCOL DIMETHACRYLATE	Guinea pig	Mild irritant

3M Unitek Transbond XT Primer (712-034)	12/29/17	
-----------------------------------------	----------	--

BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Not	Minimal irritation
	available	
TRIPHENYLANTIMONY	Rabbit	Minimal irritation
HYDROQUINONE	Human	Minimal irritation
	and	
	animal	

Serious Eye Damage/Irritation

Name	Species	Value
TRIETHYLENE GLYCOL DIMETHACRYLATE	Professio	Moderate irritant
	nal	
	judgeme	
	nt	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Not	Moderate irritant
	available	
TRIPHENYLANTIMONY	Rabbit	Mild irritant
HYDROQUINONE	Human	Corrosive

Skin Sensitization

Name	Species	Value
TRIETHYLENE GLYCOL DIMETHACRYLATE	Human	Sensitizing
	and	
	animal	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Guinea	Sensitizing
	pig	
HYDROQUINONE	Guinea	Sensitizing
	pig	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
TRIETHYLENE GLYCOL DIMETHACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
HYDROQUINONE	In Vitro	Some positive data exist, but the data are not sufficient for classification
HYDROQUINONE	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
TRIETHYLENE GLYCOL DIMETHACRYLATE	Dermal	Mouse	Not carcinogenic
HYDROQUINONE	Dermal	Mouse	Not carcinogenic
HYDROQUINONE	Ingestion	Multiple	Some positive data exist, but the data are not
		animal	sufficient for classification
		species	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
TRIETHYLENE GLYCOL DIMETHACRYLATE	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
TRIETHYLENE GLYCOL DIMETHACRYLATE	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
TRIETHYLENE GLYCOL DIMETHACRYLATE	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation

3M Unitek Transbond XT Primer	(712-034)) 12/29/17
-------------------------------	-----------	------------

BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Ingestion	Not classified for female reproduction	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Ingestion	Not classified for male reproduction	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Ingestion	Not classified for development	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
HYDROQUINONE	Ingestion	Not classified for female reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
HYDROQUINONE	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
HYDROQUINONE	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDROQUINONE	Ingestion	nervous system	May cause damage to organs	Rat	NOAEL Not available	not applicable
HYDROQUINONE	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg	not applicable

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
TRIETHYLENE GLYCOL DIMETHACRYLATE	Dermal	kidney and/or bladder blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Ingestion	endocrine system liver nervous system kidney and/or bladder	Not classified	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
HYDROQUINONE	Ingestion	blood	Not classified	Rat	NOAEL Not available	40 days
HYDROQUINONE	Ingestion	bone marrow liver	Not classified	Rat	NOAEL Not available	9 weeks
HYDROQUINONE	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 50 mg/kg/day	15 months
HYDROQUINONE	Ocular	eyes	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

indrof its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Serious eye damage or eye irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

Page 9 **of** 10

3M Unitek Transbond XT Primer (712-034) 12/29/17

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:11-9309-3Version Number:9.01Issue Date:12/29/17Supercedes Date:02/25/16

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com

Page 10 of 10



Safety Data Sheet

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 11-9681-5
 Version Number:
 7.01

 Issue Date:
 01/19/18
 Supercedes Date:
 02/25/16

SECTION 1: Identification

1.1. Product identifier

Transbond LR Light Cure Adhesive (712-038)

Product Identification Numbers

70-2020-8950-7

1.2. Recommended use and restrictions on use

Recommended use

Orthodontic use, Orthodontic use

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Oral Care Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B. Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Page 1 of 10

Pictograms



Hazard Statements

Causes eye irritation.

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
SILANE TREATED QUARTZ	100402-78-6	75 - 85 Trade Secret *
BISPHENOL A DIGLYCIDYL ETHER	1565-94-2	5 - 15 Trade Secret *
DIMETHACRYLATE		
TRIETHYLENE GLYCOL DIMETHACRYLATE	109-16-0	5 - 15 Trade Secret *
DICHLORODIMETHYLSILANE REACTION	68611-44-9	< 2 Trade Secret *
PRODUCT WITH SILICA		
N,N-DIMETHYLBENZOCAINE	10287-53-3	< 0.30 Trade Secret *
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	58109-40-3	< 0.1 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms

Page 2 of 10 01/19/18

develop, get medical attention.

Eve Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide Condition

During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not get in eyes.

Page 3 of 10

01/19/18

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:Specific Physical Form:
Paste

Odor, Color, Grade:
Off white paste, slight acrylate odor
No Data Available

рH Not Applicable Melting point No Data Available **Boiling Point** Not Applicable **Flash Point** No flash point **Evaporation rate** Not Applicable Flammability (solid, gas) Not Classified Flammable Limits(LEL) Not Applicable Flammable Limits(UEL) Not Applicable Vapor Pressure Not Applicable **Vapor Density** Not Applicable **Density** No Data Available

Specific Gravity Approximately 1.95 g/ml [Ref Std:WATER=1]

Solubility in Water Nil

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data Available

Page 4 of 10

Transbond LR Light Cure Adhesive (712-038)

01/19/18

Decomposition temperatureNo Data AvailableViscosityNot ApplicableVolatile Organic CompoundsNo Data AvailablePercent volatileNo Data AvailableVOC Less H2O & Exempt SolventsNo Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Light

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
SILANE TREATED QUARTZ	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILANE TREATED QUARTZ	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
SILANE TREATED QUARTZ	Ingestion	Rat	LD50 > 5,110 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Dermal	Professio	LD50 estimated to be 2,000 - 5,000 mg/kg
		nal	
		judgeme	
		nt	
TRIETHYLENE GLYCOL DIMETHACRYLATE	Dermal	Professio	LD50 estimated to be > 5,000 mg/kg
		nal	
		judgeme	
TRICTIVE FUE OF ACOT DRICTILL OBSE ATE	T	nt	1.050 10.027 //
TRIETHYLENE GLYCOL DIMETHACRYLATE	Ingestion	Rat	LD50 10,837 mg/kg
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
DICHLORODIMETHYLSILANE REACTION PRODUCT	Inhalation-	Rat	LC50 > 0.691 mg/l
WITH SILICA	Dust/Mist		
	(4 hours)		
DICHLORODIMETHYLSILANE REACTION PRODUCT	Ingestion	Rat	LD50 > 5,110 mg/kg
WITH SILICA	Ū		
N,N-DIMETHYLBENZOCAINE	Dermal	Rat	LD50 > 2,000 mg/kg
N,N-DIMETHYLBENZOCAINE	Ingestion	Rat	LD50 > 2,000 mg/kg
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Ingestion	Rat	LD50 32 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
	-	
SILANE TREATED QUARTZ	Rabbit	No significant irritation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Not	Minimal irritation
	available	
TRIETHYLENE GLYCOL DIMETHACRYLATE	Guinea	Mild irritant
	pig	
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Rabbit	No significant irritation
N,N-DIMETHYLBENZOCAINE	Rabbit	No significant irritation
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
SILANE TREATED QUARTZ	Rabbit	No significant irritation

Page 6 of 10

BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Not	Moderate irritant
	available	
TRIETHYLENE GLYCOL DIMETHACRYLATE	Professio	Moderate irritant
	nal	
	judgeme	
	nt	
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Rabbit	No significant irritation
N,N-DIMETHYLBENZOCAINE	Rabbit	Mild irritant
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
SILANE TREATED QUARTZ	Human	Not classified
	and	
	animal	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Guinea	Sensitizing
	pig	
TRIETHYLENE GLYCOL DIMETHACRYLATE	Human	Sensitizing
	and	
	animal	
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Human	Not classified
	and	
	animal	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
SILANE TREATED QUARTZ	In Vitro	Not mutagenic
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
TRIETHYLENE GLYCOL DIMETHACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	In Vitro	Not mutagenic
DIPHENYLIODONIUM HEXAFLUOROPHOSPHATE	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
SILANE TREATED QUARTZ	Not		Some positive data exist, but the data are not
	Specified		sufficient for classification
TRIETHYLENE GLYCOL DIMETHACRYLATE	Dermal	Mouse	Not carcinogenic
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH	Not	Mouse	Some positive data exist, but the data are not
SILICA	Specified		sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
SILANE TREATED QUARTZ	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATED QUARTZ	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SILANE TREATED QUARTZ	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Ingestion	Not classified for female reproduction	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
BISPHENOL A DIGLYCIDYL ETHER	Ingestion	Not classified for male reproduction	Mouse	NOAEL 0.8	premating &

Page 7 **of** 10

01/19/18

DIMETHACRYLATE				mg/kg/day	during gestation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Ingestion	Not classified for development	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
TRIETHYLENE GLYCOL DIMETHACRYLATE	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
TRIETHYLENE GLYCOL DIMETHACRYLATE	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
TRIETHYLENE GLYCOL DIMETHACRYLATE	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
DIPHENYLIODONIUM HEXAFLUOROPHOSPH	Inhalation	respiratory irritation	Not classified	Not available	Irritation Equivocal	
ATE						

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SILANE TREATED QUARTZ	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE	Ingestion	endocrine system liver nervous system kidney and/or bladder	Not classified	Mouse	NOAEL 0.8 mg/kg/day	premating & during gestation
TRIETHYLENE GLYCOL DIMETHACRYLATE	Dermal	kidney and/or bladder blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks
DICHLORODIMETHYLS ILANE REACTION PRODUCT WITH SILICA	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material

and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Serious eye damage or eye irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

Transbond LR Light Cure Adhesive (712-038)

01/19/18

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 11-9681-5
 Version Number:
 7.01

 Issue Date:
 01/19/18
 Supercedes Date:
 02/25/16

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com

Page 10 of 10